PANDAWA
COCO INDONESIA

PRODUCT SPEC SHEET
EDITION NOVEMBER 2026

Sawdust Charcoal Briquettes

Utility Series (mixed grades B/C/D)

For furnaces, boilers and industrial heating

Raw material. 100% hardwood sawdust charcoal, pressed into hexagonal logs with a centre hole.

KEY SPECIFICATIONS

Ash content	**6–9%**
Burn time	**2–6 hours***

FORM & SIZE

Shape	Hexagonal log, diameter 40–50 mm, centre hole 10–15 mm
Length	5–25 cm, mixed

PACKING

Bags	5 / 10 / 20 / 25 kg, woven or PE industrial bags
Optional	Kraft or printed OEM bags
Private label	Your brand on the bag

QUALITY CONTROL ON EVERY ORDER

1. **Before production**
   Raw material check: hardwood sawdust, purity
2. **During production**
   Density and hardness, length sorting, controlled drying
3. **Before loading**
   Ash and moisture test, burn test, packing check, loading photos and video

CONTAINER LOADING

20ft approx. 18–20 MT · **40ft** approx. 24–26 MT

EXPORT DETAILS

HS code	Heading 4402 (wood charcoal)
Shipping	IMDG class 4.2 (UN1361); self-heating test arranged for the carrier

TRADE TERMS

Incoterms	FOB, CFR or CIF
Minimum order	Depends on product and packing; confirmed in the quotation
Payment	T/T (deposit, balance before B/L release) for initial orders; L/C discussable for qualified volumes

* Burn time depends on test method and size. Values are typical ranges. The agreed specification is written into your quotation, and test results and loading photos are shared with you before the container sails. Pandawa Coco Indonesia is an export trading house working with audited manufacturing partners in Indonesia.

Send us your target specification and destination port.

sales@pandawacoco.com
www.pandawacoco.com